



BEARING ITALIA S.P.A

440 mm x 650 mm x 157 mm NTN 23088BC3
Double row spherical roller bearings

Bearing No. 23088BC3

d	440 mm
D	650 mm
B	157 mm
d2	508 mm
D1	584.6 mm
rs min	6 mm
Number of lubrication holes	8
b	20 mm
k	12 mm
e	0.24
Y1	2.85
Y2	4.24
Y0	2.78
Radial clearance class	C3
Dynamic load, C	3,300 kN
Static load, C0	6,850 kN
Fatigue limit load, Cu	838 kN
Nref	610 rpm
Nlim	800 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	10.62 Hz

23088BC3 Bearing 2D drawings and 3D CAD models



BEARING ITALIA S.P.A

Characteristic outer ring frequency, BPF0	13.16 Hz
Characteristic inner ring frequency, BRFI	15.84 Hz
da min	463 mm
Da max	627 mm
ra max	5 mm
Category	Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	180.994
EAN	4547359279122
Product Group	B04311